

CU-44X MK II CAPTURE THE SPARKLE OF SONIC BEAUTY

CU-44X MK II for a Powerful, Clear and Consistently Uncolored Sound



The CU-44X MK II is a perfect mic wherever you put it. It features an extremely accurate dual-capsule design for incredible low end and fast transients at the top delivering an overall sound that absolutely does justice to any artistic performance.

This is an outstanding mic that you can totally rely on even in the most demanding and critical situations.

The CU-44X MK II has a revolutionary design featuring two titanium matched capsules for low and high, with 100 volt internal power for super wide dynamic range and headroom.

- Transformerless design for high transient, natural and uncolored sound with vivid sonic imagery
- Internal high voltage power supply for wide dynamic range and headroom
- Dual coherent titanium membranes, for bass and HF, immune to the effects of humidity and temperature change
- Smooth cardioid polar pattern
- Withstands high SPL
- Flat frequency response (20Hz to 30kHz) totally flat on axis and at 90 degrees – essential in maintaining sonic transparency
- Low noise
- Perfect for vocals, overheads, and acoustic instruments



Shown with
included S-44X
Shock Mount
Suspension

CU-44X MK II

Transformerless, Cardioid Double Condenser Microphone




“On a list of mics I would never want to be without, my Sanken CU-44X MkII is at the top. In a world of specialization, it simply does everything well. It’s my first choice on vocals, drum overheads, pianos and strings. The dual capsule design, coupled with high SPL durability make it second to none.”

Grammy Award-Winning Frank Filipetti


SPECIFICATIONS

Model Name	CU-44X MKII
Transducer	DC biased condenser
Directivity	Cardioid
Frequency response	20Hz – 30kHz
Sensitivity	-34dB(20mV, 0dB=1V/Pa)
Equivalent noise level (IEC)	15dB-A
Max SPL(1% THD)	140dB SPL
Output impedance(1kHz)	150 ohms
Powering	+48V±4V phantom
Current consumption	4mA
Weight	430g / .95lbs
Dimensions	156mm x 45.5mm (D) 6.14in x 1.79in (D)
Surface finish	Matte black
Connector	XLR-3-12C(M) equivalent 1: GND, 2: Hot, 3: Cold

POLAR PATTERN CU-44X MKII



FREQUENCY RESPONSE CU-44X MKII



Sanken Chromatic 323.845.1171
Exclusive Distribution by plus24
8974 Kramerwood Place
Los Angeles, CA 90034

Copyright © 2002-2018
plus24 All rights reserved.

